



MEGGITT


| Ground Fueling Products

Steve Minier

Venturi


Venturi

The purpose of a Venturi is to compensate for the loss of pressure from the outlet of the venturi to the aircraft.




How The Venturi Works

- The venturi sends simulated nozzle pressure as a control signal to the pressure control valves and the panel mounted “nozzle pressure” gauge.
- To address the pressure loss the actual pump pressure is normally set at 80-90 psi to compensate for the loss.



AIRCRAFT FUELER
FUELING S/D, PTO ENGAGED

Venturi



AIRCRAFT FUELER
FUELING S/O, PTD ENGAGED

Pressure Loss




Typical pressure loss at 450 GPM

- Nozzle, 100 mesh screen and standard disconnect 14 psi.
- 2 1/2 " X 50' refueling hose 18 psi.
- Total compensation 32 psi.
 - Not including the piping and hose reel...

Venturi

Leading Engineering
Solutions that Lead
Better Tomorrow



Venturi Selection



abling Engineering
eakthroughs that Lead
a Better Tomorrow

- There isn't one venturi that fits all applications, picking the correct venturi is determined by a few factors: Flow rate, pressure compensation and pipe diameter.
- Always choose a venturi that has more compensation than the system requires. By doing this you can bleed off high signal pressure when adjusting the venturi.
- To properly achieve compensation the venturi should be installed with a minimum of straight pipe 4 times the pipe diameter both upstream and downstream. Less than this may reduce the available compensation.
- All sense lines must be 3/8" ID to allow the venturi to properly send a signal to the control valves.

Venturi Selection



Leading Engineering
Breakthroughs that Lead
Better Tomorrow


- The pressure at the nozzle is true nozzle pressure. Once the venturi is properly selected and adjusted both your test manifold and unit panel gauges will read the same.
- With the venturi properly adjusted the system will deliver the maximum flow rate at the proper pressure to protect the aircraft.
- If the length or diameter of the product hose is changed you will need to re-adjust the venturi.
- If a HECV is mounted to the nozzle it must be blocked out during set-up of the venturi.
- Always verify the sense lines are:
 - Air Free
 - Kink free
 - Leak Free
 - Properly Routed

Test Set-up



Venturi Installation...

Enabling Engineering
Breakthroughs that Lead
to a Better Tomorrow





MEGGITT

| Ground Fueling Products

Steve Minier

Single Point Nozzle

NOZZLE REPAIR

- ✓ Recommended tools of the trade
- ✓ Manufactures tools for teardown, rebuilding and testing



NOZZLE REPAIR

- ✓ Ample spare parts and a complete rebuild kit from the manufacturer



Maintenance Manual

UNDERWING REFUELLING NOZZLE

F117 Series

MMF117

Revision 2.0

27 September 2013



Meggitt (North Hollywood), Inc. Proprietary Information

The information contained in this document is disclosed in confidence. It is the property of Meggitt (North Hollywood), Inc. and shall not be used, disclosed to others, or reproduced in whole or in part without the express written consent of Meggitt (North Hollywood), Inc. If consent is given, this notice shall appear in any such reproduction. These commodities, technology, or software were exported from the United States in accordance with the export administration regulations. Diversion contrary to U.S. law is prohibited.
SENSITIVE BUT UNCLASSIFIED-EXPORT CONTROLLED-EAR RESTRICTED.
These commodities, technology or software are exported from the United States of America in accordance with the Export Administration Regulations. ECCN EAR99. Diversion contrary to U.S. law is prohibited.
Copyright © 2013 Meggitt (North Hollywood), Inc.

Meggitt Control Systems

Our product complements services:
Aerospace & Defense | Transportation & Logistics | Industrial & Manufacturing | Process & Environmental Control

MEGGITT
SPECIALIZING IN
extreme environments



EXAMINATION OF PRODUCT

- The nozzle shall be inspected for compliance to the requirements of materials, workmanship, dimensions, configuration, markings, etc.
- The nozzle shall be free of dirt, grease, chips and other foreign matter as evidenced by visual examination.

Teardown & Inspection:

- Inspect for defects or damage that needs to be addressed prior to teardown

General:

- Complete all tests using Stoddard solvent or equivalent as the test fluid, supplied by 0 to 120 psi

NOZZLE TESTING

Testing after the nozzle has been completely rebuilt

TEST PROCEDURES

Mechanical Test

- ✓ Install a test fixtures on both the nozzle inlet and 3-lug test fixture.
- ✓ Install a test plug in the inlet side to allow the bleeding air out through the test port.
- ✓ The nozzle shall freely engage and disengage with the 3-lug flange, there shall be no binding of the nozzle operating handle.
- ✓ With the nozzle connected to the 3-lug test fixture, actuate the flow control handle 5 times. The nozzle must operate freely with no mechanical interference or binding.



NOZZLE TESTING

Leakage Test (Closed Position)

- ✓ With the flow control handle in the closed position apply 5 psi fluid pressure while bleeding the air out through the test plug on the nozzle.
- ✓ Apply pressure to the nozzle at 10, 60 then 120 psi. Each test should be held for 3 minutes per test.
- Note; Look for evidence of external leakage through the nozzle body, shaft seals, swivel or nose seal area.
- ✓ Decrease pressure to 0 psi.



NOZZLE TESTING

Leakage Test (Open Position)

- ✓ Engage and lock the nozzle to the 3-lug test fixture.
- ✓ Rotate the flow control handle to the open position and apply 5 psi fluid pressure bleeding out the air through the test plug in the nozzle.
- ✓ Apply pressure to the nozzle at 10, 60 then 120 psi. Each test should be held for 3 minutes per test.
- Note; Open and close the flow control handle 3 times during each test pressure and check for leaks at the shaft seals and nose seal area.
- ✓ Decrease test pressure to 0 psi.
- ✓ Close the flow control handle



NOZZLE TESTING

Final Test:

Leakage Test (Closed Position Disconnected)

- ✓ Remove nozzle from 3-lug test fixture and wipe down the poppet face.
- ✓ Apply pressure to the nozzle at 10, 60 then 120 psi. Each test should be held for 3 minutes per test.
- Note; Look for leaks between the poppet and the nose seal.
- ✓ Decrease test pressure to 0 psi.
- ✓ Remove nozzle from test fixture.



Thank You

Point of Contact:



Steve Minier
Territory Manager
North & South America
Mobile : +1 (248)-952-7554
steven.minier@parker.com

